



Installation

1. Set-up the sewerage d 110 mm finished with end-neck of the toilet. The end-neck must be at the floor level or up to 25 mm beneath the floor. It must not protrude over the floor.
2. Place the closet on prepared outlet and mark the anchor points. These points are accessible after unscrewing the protecting covers of anchoring bolts in the lower part of the casing.
3. Drill the holes for dowels d 12. Supplied dowells are intended for fixing the toilet to the concrete floor. When using another type of floor it is necessary to select the appropriate anchor elements.
4. Place the toilet on the outlet and water supply pipe.
5. Tighten the toilet well to the floor by means of attached screws.
6. Screw back the protecting covers of anchoring bolts.

Complete delivery

- | | |
|---|-------|
| • Stainless steel toilet with seat | 1 pc |
| • Inlet sealing gasket | 1 pc |
| • Dowel d 12, anchoring bolts M8 x 90, washer | 2 pcs |

Maintenance and cleaning

- The device was made from the stainless steel of quality corresponding with ČSN 17 240 (AISI 304) standard and, therefore, it must not be operated in chemically-aggressive environment and
- **Preparations containing chlorine must not be used for its cleaning!!**
- Cleaning agents by WÜRTH are recommended:
 - Metal renewal agent - Order No. 893 121 1
 - Stainless steel spray treatment - Order No. 0893 121 – K.
- If corrosion has already occurred, it can be removed with a cleaner INNOSOFT B 570 from the company Emergo.