



Catalog sheet

BSNZ 01 INV

Safety stainless steel wallmounted toilet for physically disabled

The **BSNZ 01 INV** is a wallmounted stainless steel toilet with a matte finish. Its mounting holes match those of a standard ceramic toilet. It can be installed as a complete unit with the **BSAZ 01** automatic safety flushing system and the **KZ 1** cantilever, or with the **BSAZ 5** mechanical stainless steel antivandal flushing system with in-wall module. Due to its damage resistance, the **BSNZ 01** is designed primarily for the modernization of prisons, diagnostic centers, detention cells, and similar facilities—offering maximum water savings when used with the **BSAZ 01** flushing system. You can find other variants of toilets in the stainless steel toilets or stainless steel security toilets section. The toilets are made of stainless steel of class ČSN 17240 (AISI 304). Other materials on request (e.g. AISI 316). For the treatment of stainless steel products, we recommend using Würth detergents – material preservation (order no. 0893 121 K), material cleaning (order no. 893 121 I).



BSNZ 01 INV

Complete delivery

- Stainless steel WC
- Anchoring material

Available variants

- BSNZ 01 INV Safety stainless steel wallmounted toilet for physically disabled

Technical details

- | | |
|----------------------------------|-------------|
| • Water inlet | d= 34-50 mm |
| • Min. water flow capacity | 70 l/min |
| • Outlet | d = 90 mm |
| • Required spacing between bolts | 180 mm |
| • Weight | 24 kg |



Construction readiness requirements

- Set-up water inlet $d = 34\text{--}50\text{ mm}$ and chosen sealing
- Set-up outlet $d = 90\text{ mm}$ as per diagram
- Set-up the cantilever or other system for hanging the closet

Diagram

